


The SPOT™ Pursuit Slider delivers both true color and high sensitivity monochrome imaging in one digital camera. It offers superior quantum efficiency and Peltier cooling, optimizing sensitivity for low light scientific applications. This compact camera provides 14-bit digitization with multiple readout speeds for recording dynamic events. The many applications for this versatile camera include bright-field color imaging, GFP imaging, immunofluorescence, ion tracking, and 3D deconvolution.

The SPOT Pursuit includes SPOT Basic software (Windows® and Mac® OS) for real-time image preview and acquisition. Drivers are available for third party imaging software applications, and Software Development Kit (SDK) is available at no charge for easy integration with custom applications. Advanced triggering enables precise synchronization with peripherals, and USB 2.0 connectivity affords effortless installation on computers and laptop portability.



# Pursuit™ USB 1.4 Mp SLIDER



## Features

## Benefits

Dual Mode Slider Mechanism	Provides both 3-shot high resolution and high sensitivity color quantitative monochrome imaging in one camera
>10 fps Image Capture	High speed, high resolution image capture
8 e <sup>-</sup> Read Noise	Excellent low light detection limit and SNR
Enhanced IR Mode	Increased sensitivity, for wavelength > 525nm
No Glow Mode	Turns off all sources of On-CCD circuit glow during exposure. Important for long exposures.
USB 2.0	Plug and play cable connection, no frame grabber card needed
-25° C Cooling	Suppresses dark current noise
Mac® and Windows® OS	Choose your OS environment




**SPOT Imaging Solutions™**  
A division of Diagnostic Instruments, Inc.

## Specifications

Resolution	1.4 Mp
Sensor Type	Sony ICX285AL CCD monochrome
Shutter	Global electronic
Active Pixels	1360 x 1024
Pixel Size	6.45 µm x 6.45 µm
Optical Format	2/3"
Active Imager Size	8.77mm (H) x 6.60mm (V) 10.97mm diagonal
Exposure Time	0.5ms – 1500sec
Anti-Blooming	100x minimum
Binning	2 x 2, 3 x 3, 4 x 4, 8 x 8
Region of Interest	User selectable, 50 x 50 to full resolution
Read Noise	8 e- RMS typical
Dark current	0.045 e/p/s
Full Well Depth	>16,000 e- (no binning) >24,600 e- (with binning)
Non-linearity	<1%
A-D Converter	14-Bit @ 20 MHz DCS
Saving Bit Depth	8, 12 or 16 bits/channel (24, 36 or 48 bit color)
Analog Gain	0.65, 1
Cooling	-25° C differential from ambient via computer controlled fan cooled thermoelectric cooler with hermetically sealed, fan cooled heat sink
Lens Mount	F-mount
Computer Interface	USB 2.0
Triggers	Camera ready output (TTL) External trigger input (TTL) Exposure sync output (TTL)
Tripod Mount	1/4"-20 (sold separately)
Weight	2.4 lbs (1.09 kg)
Size	5.5" W x 4.3" D x 2.7" H (139mm x 109mm x 68mm)
Power Requirements	100-240 VAC 1A
Operating Environment	0 to 50°C, 95% relative humidity (non-condensing)
Storage Temperature	-20 to 60°C
Certifications	CE, FCC Class A, EN60950, RoHS

## Quantum Efficiency



## Captured Frame Rates

Binning level	Region of interest				
	1360x1024	640x480	512x512	256x256	50x50
None	10.9	21.5	20.5	36.2	92.4
2 x 2	20.1	37.3	35.9	58.3	114.0
3 x 3	28.0	49.4	48.2	73.8	124.6
4 x 4	34.8	59.2	57.7	84.6	130.0
8 x 8	55.3	83.6	83.2	108.7	138.8

\*1ms exposure with post-processing deferred, taken with 2.6 Ghz Xeon processor running Windows XP. Capture rates on other computers OS platforms may vary (Monochrome Mode).

## SPOT Software

SPOT Basic Software Features	Color Live mode viewing window with controls Image capture window Image capture setups are user defined, named and saved Auto or manual exposure for Live and captured images Auto white balance Spot or average metering Flatfield correction Annotation Calibration mark Measurement tools Image enhancement tools Sequential image capture and playback Report generator Interactive print dialog Help menu 3rd Party Software Interface: Standard Twain for Windows®, SPOT Image Capture Application & Apple Event for Mac®
Computer Operating System Compatibility	Windows®: XP SP3 (32-bit), Vista (32 or 64-bit), 7 (32 or 64-bit) and 8 (32 or 64-bit) Mac®: OS 10.6 - 10.8
Minimum Computer Requirements	PC: 1GHz Pentium 4 (or equivalent x86 SSE2 processor), 1 GB RAM, USB 2.0 port Mac®: Intel processor, 1 GB RAM, USB 2.0 port Mac® and PC video: 24-bit color @ 1024 x 768 resolution
SPOT Advanced Software	Available (includes macro feature, floating taskbars, custom dialogs and image archiving database)
SPOT Advanced Software Modules (Optional)	Available (adds image display intensity scaling, peripheral device control, extended depth of focus and extended third party interface)
Software Development Kit	Available for Mac® and Windows®
Native Drivers for 3rd Party Software	Available (call or visit our website)

## Items Included

Camera Head	With lens cap
USB2 Cable	Carries data
Power Supply	With power cord, 5.91" (150mm) x 2.76" (70mm) x 1.38" (35mm), 1.36 lbs. (600g)
Quick Start Installation Guide	Instructions on how to get up and running quickly
Software CD	Includes SPOT Basic software and User Guide
Warranty	2 years from date of purchase

Catalog Number	C-Mount	F-Mount
Pursuit 1.4 Mp USB Slider	NA	PR3440



Specifications are typical and subject to change.

**SPOT Imaging Solutions™**  
A division of Diagnostic Instruments, Inc.

6540 Burroughs Avenue • Sterling Heights • MI • 48314-2133  
phone: 586.731.6000 • fax: 586.731.6469 • website: www.spotimaging.com  
Data Sheet: Pursuit USB Slider